






Series 132

XTS

C

2800rpm

Ø 24mm



AR\_s132-02\_Ø15

05/06/2026



Series 132

XTS

C

2800rpm

ø 24mm

| P  | Code    | Description    |                   | Q | Assembly prescription               | Validity | P  | Code    | Description    |              | Q | Assembly prescription        | Validity |
|----|---------|----------------|-------------------|---|-------------------------------------|----------|----|---------|----------------|--------------|---|------------------------------|----------|
| 1  | 1269221 | Head assembly  | Ø 15              | 1 |                                     |          | 75 | 1320330 | Bushing        |              | 1 |                              |          |
| 2  | 1320022 | Head           |                   | 1 |                                     |          | 76 | 1320370 | Bearing        |              | 1 |                              |          |
| 3  | 820361  | Plug           | 1/2" G brass      | 1 | C=40Nm                              |          | 77 | 1260790 | Ring           | seeger Øi 52 | 1 |                              |          |
| 4  | 180101  | O-ring         | Ø 17,5x2          | 1 | Lubricate with grease Molykote PG54 |          | 78 | 1266740 | Cover          |              | 1 |                              |          |
| 5  | 1980740 | Plug           | 3/8" G brass      | 1 | C=20Nm                              |          | 85 | 1321160 | Shaft          | 5 marked     | 1 |                              |          |
| 6  | 740290  | O-ring         | Ø 14x1,78         | 1 | Lubricate with grease Molykote PG54 |          | 87 | 1321190 | Bearing        |              | 1 | Assemble with tool [1780610] |          |
| 7  | 620301  | Plug           | 1/8" G            | 1 | Loxeal 55-14                        |          | 88 | 1321080 | Ring           |              | 1 |                              |          |
| 9  | 1260162 | Plug           |                   | 6 | C=34Nm                              |          | 89 | 480671  | Ring           | seal         | 1 | Assemble with tool [1781000] |          |
| 10 | 960160  | O-ring         | Ø 17,86x2,62      | 6 | Lubricate with grease Molykote PG54 |          | 90 | 390430  | Screw          | TE M6x25     | 1 | C=24Nm                       |          |
| 11 | 1269050 | Complete valve |                   | 6 |                                     |          | 91 | 780230  | Washer         |              | 1 |                              |          |
| 12 | 880830  | O-ring         | Ø 15,54x2,62      | 6 | Lubricate with grease Molykote PG54 |          | 98 | 1263890 | Foot           |              | 2 |                              |          |
| 20 | 1520120 | Ring           | support Ø 15      | 3 |                                     |          | 99 | 1260470 | Screw          | TE M8x10     | 4 | C=24Nm                       |          |
| 21 | 1271650 | Water seal     | Ø 15              | 3 | Lubricate with grease Molykote PG54 |          | A  | 1864    | Valve kit      |              | 1 |                              |          |
| 22 | 1260151 | Piston guide   | Ø 15              | 3 |                                     |          | B  | 2628    | Piston kit     | Ø 15         | 1 |                              |          |
| 23 | 1260420 | O-ring         | Ø 26,70x1,78      | 3 | Lubricate with grease Molykote PG54 |          | C  | 1860    | Oil seal kit   |              | 1 |                              |          |
| 24 | 1260440 | Water seal     | Ø 15              | 3 | Lubricate with grease Molykote PG54 |          | E  | 1866    | Water seal kit | Ø 15         | 1 |                              |          |
| 25 | 1260460 | Oil seal       |                   | 3 |                                     |          | E  | 2029    | Water seal kit | Ø 15 Viton   | 1 |                              |          |
| 40 | 1320010 | Pump body      |                   | 1 |                                     |          |    |         |                |              |   |                              |          |
| 41 | 680570  | Screw          | TCEI M6x60        | 6 | C=10Nm                              |          |    |         |                |              |   |                              |          |
| 42 | 1381550 | Washer         |                   | 6 |                                     |          |    |         |                |              |   |                              |          |
| 43 | 880130  | Oil plug       | with oil dipstick | 1 |                                     |          |    |         |                |              |   |                              |          |
| 44 | 1980740 | Plug           | 3/8" G brass      | 1 | C=20Nm                              |          |    |         |                |              |   |                              |          |
| 45 | 740290  | O-ring         | Ø 14x1,78         | 1 | Lubricate with grease Molykote PG54 |          |    |         |                |              |   |                              |          |
| 46 | 1260040 | Oil seal       |                   | 1 |                                     |          |    |         |                |              |   |                              |          |
| 47 | 1260760 | Screw          | TCEI M5x20        | 6 | C=5,4Nm                             |          |    |         |                |              |   |                              |          |
| 50 | 1260110 | Nut            | M8                | 3 | C=12Nm / Loxeal 55-14               |          |    |         |                |              |   |                              |          |
| 51 | 1260100 | Washer         |                   | 3 |                                     |          |    |         |                |              |   |                              |          |
| 52 | 1260120 | Piston         | Ø 15              | 3 |                                     |          |    |         |                |              |   |                              |          |
| 53 | 480480  | O-ring         | Ø 4,48x1,78       | 3 |                                     |          |    |         |                |              |   |                              |          |
| 54 | 1260091 | Plate          |                   | 3 |                                     |          |    |         |                |              |   |                              |          |
| 55 | 1260070 | Piston         | guide             | 3 |                                     |          |    |         |                |              |   |                              |          |
| 56 | 1260080 | Pin            |                   | 3 |                                     |          |    |         |                |              |   |                              |          |
| 57 | 1260060 | Connecting-rod | aluminium         | 3 |                                     |          |    |         |                |              |   |                              |          |
| 65 | 1329010 | Cover          | complete          | 1 |                                     |          |    |         |                |              |   |                              |          |
| 66 | 1260430 | Ring           |                   | 1 |                                     |          |    |         |                |              |   |                              |          |
| 67 | 1780690 | Plate          |                   | 1 |                                     |          |    |         |                |              |   |                              |          |
| 68 | 1260250 | Level gauge    |                   | 1 |                                     |          |    |         |                |              |   |                              |          |
| 69 | 1140450 | O-ring         | Ø 20,24x2,62      | 1 | Lubricate with grease Molykote PG54 |          |    |         |                |              |   |                              |          |

Revision: 1

Oil type: SAE 15W40

Validity: &lt; XX/YY = From week/year

Date: 05/06/2026

Oil quantity: 0,280 Kg

C= Tightening torque (Tolerance +0 ÷ -10%)

\* = Not present for electric pump