




Series 320

RCA-M

E

1750rpm

ø 5/8"



AR_s320-05_Ø15

05/06/2026



Series 320

RCA-M

E

1750rpm

ø 5/8"

P	Code	Description		Q	Assembly prescription	Validity	P	Code	Description		Q	Assembly prescription	Validity
1	3209202	Head assembly	Ø 15	1			78	3201860	Ring	Ø 51,8x0,5	1		
2	3200100	Head		1			79	395081	O-ring	Ø 47,30x2,62	1		
3	820361	Plug	1/2" G brass	1	C=40Nm		80	3209615	Oil level assembly		1		
4	180101	O-ring	Ø 17,5x2	1	Lubricate with grease Molykote PG54		81	3200070	Support		1		
5	1980740	Plug	3/8" G brass	1	C=20Nm		82	1200430	Screw	TCEI M6x16	8	C=10Nm / Loxeal 55-14	
6	740290	O-ring	Ø 14x1,78	1	Lubricate with grease Molykote PG54		85	3200880	Shaft	13 marked	1		
9	3200110	Plug		6	C=24,5Nm / Loxeal 55-14		87	1321190	Bearing		1	Assemble with tool [1780610]	
10	1200690	O-ring	Ø 15,6x1,78	6	Lubricate with grease Molykote PG54		89	480671	Ring	seal	1	Assemble with tool [1781000]	
11	3209050	Complete valve		6			97	1322640	Washer		4		
12	394280	O-ring	Ø 12,42x1,78	6	Lubricate with grease Molykote PG54		98	3200210	Foot		2		
20	2760220	Ring	support Ø 15	3			99	850250	Screw	TCEI M8x12	4	C=24,5Nm	
21	1342761	Water seal	Ø 15	3	Lubricate with grease Molykote PG54		A	42494	Valve kit		1		
22	3200160	Piston guide	front Ø 15	3			B	42475	Piston kit	Ø 15	1		
23	3200690	Gasket	Ø 15	3	Lubricate with grease Molykote PG54		C	42474	Oil seal kit		1		
24	3200700	Ring	anti-extrusion	3			E	42476	Water seal kit	Ø 15	1		
25	770590	O-ring	Ø 21,95x1,78	3	Lubricate with grease Molykote PG54		F	42495	Gasket kit		1		
26	3200150	Piston guide	rear Ø 15	3			G	2191	Support ring kit	Ø 15	1		
39	1260460	Oil seal		3									
40	3200010	Pump body		1									
41	800410	Screw	TCEI M6x40	8	C=10,4Nm								
42	1381550	Washer		8									
43	3201890	Oil plug	with oil dipstick	1									
46	2760280	O-ring	Ø 101,27x2,62	1									
47	3200220	Screw	TCEI 6x16	4	C=8Nm								
50	1260110	Nut	M8	3	C=12Nm / Loxeal 55-14								
51	1260100	Washer		3									
52	1260120	Piston	Ø 15	3									
53	1260091	Plate		3									
54	480480	O-ring	Ø 4,48x1,78	3									
55	3200060	Piston	guide	3									
56	1780050	Pin		3									
57	3200040	Connecting-rod	aluminium	3	Lubricate with grease Molykote G807								
65	3200030	Cover		1									
70	820510	O-ring	Ø 10,82x1,78	1									
71	880581	Plug	1/4" G brass	1	C=15Nm / Loxeal 55-14								
75	1780490	Bearing		1									
76	1260790	Ring	seeger Øi 52	2									
77	1780550	Ring	seeger Øe 20	1									

Revision: 1

Oil type: SAE 15W40

Validity: < XX/YY = From week/year

Date: 05/06/2026

Oil quantity: 0,260 Kg

C=Tightening torque (Tolerance +0 ÷ -10%)

* = Not present for electric pump

23349 - RCA-M 0.5G15 E + F8




Series 320

RCA-M

E

1750rpm

Ø 5/8"



AR_sFlange-023

05/06/2026



Series 320

RCA-M

E

1750rpm

Ø 5/8"

P	Code	Description		Q	Assembly prescription	Validity
1	1320060	Flange	F8	1		
2	1200430	Screw	TCEI M6x16	4	C=10Nm / Loxeal 55-14	

P	Code	Description		Q	Assembly prescription	Validity
---	------	-------------	--	---	-----------------------	----------

Revision: 1

Oil type: SAE 15W40

Validity: < XX/YY = From week/year

Date: 05/06/2026

Oil quantity: 0,260 Kg

$C = \text{Tightening torque (Tolerance } +0 \div -10\%)$

* = Not present for electric pump

23349 - RCA-M 0.5G15 E + F8